

## TEROSON MS 9371B

July 2012

### PRODUCT DESCRIPTION

TEROSON MS 9371B provides the following product characteristics:

<b>Technology</b>	Silane-modified polymer
<b>Product Type</b>	Hardener component (B-component)
<b>Components</b>	One-component
<b>Cure</b>	Humidity
<b>Application</b>	Assembly
<b>Appearance</b>	White
<b>Consistency</b>	Pasty, Thixotropic
<b>Odor</b>	Characteristic

TEROSON MS 9371B is an accelerator paste.

### Application Areas:

TEROSON MS 9371B is used for accelerating Teroson-MS adhesives and sealants independent of humidity.

### TECHNICAL DATA

Density, g/cm<sup>3</sup>: approx. 1.3

### DIRECTIONS OF USE

#### Preliminary Statement:

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

#### Application:

TEROSON MS 9371B is not reactive and does not cure alone. The product is used in combination with Teroson-MS adhesives and sealants. For the processing a data sheet for the mentioned product can be requested.

### Storage:

Frost-Sensitive No  
Recommended storage temperature, °C 10 to 25  
Shelf-life (in unopened original packaging), 12 months

### ADDITIONAL INFORMATION

#### Disclaimer:

The Information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention. This datasheet replaces all former versions.

Reference 0.0

Henkel AG & Co.KGaA



40191 Düsseldorf, Germany  
Phone: +49-211-797-0  
www.henkel.com